



Xihe Series

Solar storage inverter

Efficiency

- Advanced MPPT with up to 99.9% efficiency •
- Multiple charge and discharge modes are available

Safety

- 360 degrees of security from hardware tosoftware
- Multiple safety approvals available

All in one

- Support for many types of batteries
- Supports Li-ion battery BMS communication

Farm

Reliable

- · Outputs high-quality pure sine wave AC power
- · Reliable output for long periods at rated power

User-Friendly

- Industrial design with a modern aesthetic look
- Easy to install and simple to use

Intelligent

Exclusive Li-ion battery BMS dual activation

Island

• Support for remote monitoring of operating









WhatsApp/Tel: +86 186 5518 6412 Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China Email: info@sailsolarpv.com Web: www.sailsolarpv.com



MODEL INVERTER Rated Output Power Max.Peak Power Rated Output Voltage Load Capacity of Motors Rated AC Frequency Waveform Switch Time BATTERY Battery Type Rated Battery Voltage Voltage Range Max.MPPT Charging Current Max.Mains/Generator Charging Current Max.Hybrid Charging Current **PV INPUT** Num. of MPPT Trackers Max.PV Array Power Max.Input Current Max.Voltage of Open Circuit MPPT Voltage Range UTILITY/ GENERATOR INPUT UPS mode Input Voltage Range Frequency Range **Bypass Overload Current** EFFICIENCY MPPT Tracking Efficiency Max. Battery Inverter Efficiency GENERAL Dimensions Weight Protection Degree **Operating Temperature Range** Noise **Cooling Method** Force Warranty COMMUNICATION Embedded Interfaces

External Modules (Optional) CERTIFICATION Safety CE(IEC 6210 EMC RoHS

WhatsApp/Tel:+86 186 5518 6412 Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China Email: info@sailsolarpv.com Web: www.sailsolarpv.com

Xihe-5.5KLP1-EU	CAN BE SET
5,500W	
11,000VA	
230Vac (L/N/PE single phase)	\checkmark
4HP	
50Hz/60Hz	\checkmark
Pure Sine Wave	
10ms (typical)	
Lead-acid / Li-ion / User defined	\checkmark
48V	
40 ~ 60Vdc	
100A	\checkmark
60A	
100A	
1	
6,000W	
22A	
500Vdc	
120-450Vdc	
le: 170~280Vac; APL mode: 90~280Vac	~
50/60Hz	
40A	
99.9%	
92%	
426*322*126mm (1.40*1.06*0.41ft)	
10.5kg (23.15lb)	
IP20, Indor Only	
-10°C~55°C	
≤60dB	
ed air cooling with adjustable air speed	
1.5 Years	
RS485 / USB / Dry contact	
Wi-Fi / GPRS	\checkmark
09-1)/FCC/SAA/CETL(UL1741 C22.2 NO.107.1)	
EN61000	
Ves	

Yes



CAN RE